



US009409524B2

(12) **United States Patent**
Gillis

(10) **Patent No.:** **US 9,409,524 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

- (54) **NARROW SLIDING STORAGE BIN**
- (71) Applicant: **FORD GLOBAL TECHNOLOGIES, LLC**, Dearborn, MI (US)
- (72) Inventor: **Francis Raymond Gillis**, Farmington Hills, MI (US)
- (73) Assignee: **Ford Global Technologies, LLC**, Dearborn, MI (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

6,929,305 B2 *	8/2005	Park	B60N 3/083	296/37.12
7,530,617 B2 *	5/2009	Kirner	B60K 37/06	296/37.12
7,568,601 B2	8/2009	Kogami et al.	B60R 7/04	296/37.12
8,328,265 B2 *	12/2012	Danz	B60R 7/06	296/37.12
8,740,278 B1 *	6/2014	Mally	B60N 3/102	224/281
8,857,881 B2 *	10/2014	Shimozaki	B60R 11/0235	296/37.12
2002/0101091 A1 *	8/2002	Ito	B60R 7/04	296/24.34
2003/0155786 A1 *	8/2003	Kim		
2003/0197392 A1	10/2003	Clark et al.			

(Continued)

(21) Appl. No.: **14/574,697**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Dec. 18, 2014**

DE	102007005555 A1	7/2008
DE	102007061043 A1	6/2009

(65) **Prior Publication Data**

US 2016/0176351 A1 Jun. 23, 2016

(Continued)

OTHER PUBLICATIONS

(51) **Int. Cl.**
B60R 7/06 (2006.01)
B60R 11/00 (2006.01)

English machine translation for DE102007005555.

(Continued)

(52) **U.S. Cl.**
CPC **B60R 7/06** (2013.01); **B60R 2011/0082** (2013.01)

Primary Examiner — Gregory Blankenship
(74) *Attorney, Agent, or Firm* — Vichit Chea; King & Schickli, PLLC

(58) **Field of Classification Search**
CPC B60R 7/04; B60R 7/046; B60R 7/06; B60N 3/08; B60N 3/083
USPC 296/24.34, 37.8, 37.12, 70
See application file for complete search history.

(57) **ABSTRACT**

A sliding storage compartment assembly for a motor vehicle includes a storage bin including parallel side rails defined on opposed sides thereof and a pair of outboard guides each defining a channel for slidably receiving a bin side rail therein. A housing slidably receives the bin. The housing includes parallel slots defined in opposed sidewalls thereof, with each slot being configured to receive a parallel channel defined in an outboard guide. Each sidewall of the housing includes a plurality of locator pins. Each outboard guide includes at least one cooperating two-way locator slot and at least one cooperating four-way locator aperture for aligning the outboard guide and the housing sidewall.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,355,232 A *	11/1967	Blake	B60N 3/083	312/242
5,228,611 A	7/1993	Yabuya			
5,284,314 A	2/1994	Misaras et al.			
5,303,995 A *	4/1994	Kurihara	A47B 88/0477	312/319.1
5,673,891 A	10/1997	Fujihara et al.			

19 Claims, 7 Drawing Sheets

